

COMMUNICATION & SPATIAL WONDER MORE ELEGANT THAN EVER BEFORE

THE REVOLUTION IS HERE! The JUICI is our state-of-the-art model with a touchscreen and perfect online monitoring always and everywhere through a cloud solution and direct communication with your customers combined with the CT providing valuable place on the counter.

- 4/6 drinks + chilled water
- Bag-in-Box concentrates are stored in existing furniture/base cabinet .
- Preselection CO2 – OPTIONAL (Model CO2)
- Multilingual flexible touchscreen display with the possibility to show images, videos and advertising on screen for direct communication with your customers
- 1 central drink exit (hygienic tempered glass tube) with LED lighting (RGB colours settable)
- Adjustable dispensing height
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Online monitoring (access to statistics, direct error messages and much more)
- Wifi/network connection
- Reliable and durable – premium materials, robust surfaces
- Perfect mixing result through patented MidMix® system
- Preparation for payment systems + accounting

Available in the following versions:

JUICI CT L-4, JUICI CT L-4 CO2, JUICI CT L-6,
JUICI CT L-6 CO2
Hot & Cold versions now also available!



Individual design possible



different output height possible (Modell L)



Dynamic Touchscreen

Central dispensing unit with LED



Tablemount or Wallmount

DATEN	JUICI CT L-4 STILL	JUICI CT L-4 CO2	JUICI CT L-4 Hot & Cold	JUICI CT L-6 STILL	JUICI CT L-6 CO2	JUICI CT L-6 Hot & Cold
Art. No.	frucB0501Jl	frucB0506Jl	frucB0503Jl	frucB0511Jl	frucB0516Jl	frucB0513Jl
Control-/Dispensing unit with tower	L 4	L 4	L 4	L 6	L 6	L 6
Width in mm	276 mm	276 mm	276 mm	276 mm	276 mm	276 mm
Height in mm	525 mm	525 mm	525 mm	525 mm	525 mm	525 mm
Depth in mm	175 mm	175 mm	175 mm	175 mm	175 mm	175 mm
Exit height	140 - 310 mm	140 - 310 mm	140 - 310 mm	140 - 310 mm	140 - 310 mm	140 - 310 mm
Weight	6 kg	6 kg	6 kg	6 kg	6 kg	6 kg
Product selection buttons (incl. water)	flexible(touchscreen)	flexible(touchscreen)	flexible(touchscreen)	flexible(touchscreen)	flexible(touchscreen)	flexible(touchscreen)
Automatic carafe pre-selection (Extra)	✓	✓	✓	✓	✓	✓
Flavours	4	4	4	6	6	6
Mixing ratio for concentrates	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49
Concentrates in machine	-	-	-	-	-	-
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Technics box	-	-	-	-	-	-
Width in mm	260 mm	260 mm	260 mm	260 mm	260 mm	260 mm
Height in mm	360 mm	360 mm	360 mm	360 mm	360 mm	360 mm
Depth in mm	460 mm	460 mm	460 mm	460 mm	460 mm	460 mm
Weight	max. 23 kg	max. 27 kg	max. 25 kg	max. 24 kg	max. 28 kg	max. 26 kg
Distance technics box/ dispensing unit vertical	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m
Distance technics box/ dispensing unit	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m
Distance concentrate/ technics box vertical	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m
Distance concentrate/ technics box	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m
Cooling capacity	28 l/h	28 l/h	28 l/h	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - 75°C	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar
Voltage	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	230 W	320 W	2.600 W	230 W	320 W	2.600 W
with CO2-carbonator	-	✓	-	-	✓	-
FSS ¹	✓	✓	✓	✓	✓	✓
Flowmeter (water)	✓	✓	✓	✓	✓	✓
TFT-Touchdisplay	✓	✓	✓	✓	✓	✓
Dispensing area LED light	✓	✓	✓	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓	✓	✓	✓	✓
Payment systems	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Syrup Injection Valve (SIV ²)	✓	✓	✓	✓	✓	✓
Syrup -empty message	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Control of Disinfection and Sanitation intervals	✓	✓	✓	✓	✓	✓

ALL our models are equipped with the unique and patented mixing system MidMix III.

- 1) FSS = flood security system: avoids water flood problems due to an extra safety valve on water entrance.
2) SIV = syrup injection valve for perfect mixing results

SIZE INCL. PACKAGING	JUICI CT L-4 STILL	JUICI CT L-4 CO2	JUICI CT L-4 Hot & Cold	JUICI CT L-6 STILL	JUICI CT L-6 CO2	JUICI CT L-6 Hot & Cold
Width	570 mm	570 mm	570 mm	570 mm	570 mm	570 mm
Height	670 mm	670 mm	670 mm	670 mm	670 mm	670 mm
Depth	310 mm	310 mm	310 mm	310 mm	310 mm	310 mm
Weight incl. Packaging	32 kg	36 kg	33 kg	33 kg	37 kg	34 kg
MACHINE PACKAGE/PALLET						
Europallet 80 x 120 cm	8	8	8	8	8	8
UK-size pallet 100 x 120 cm	12	12	12	12	12	12



Save
resources



Save on Warehousing
and Transport



Save
energy



Reduce CO2
emissions



FRUCTOMAT

BY ASCO DRINK MACHINES