

MIRROR, MIRROR ON THE WALL...!

THE JDM WM 4 IS OUR WALLMOUNT MODEL – DIRECT MOUNTING ON THE WALL, FOR 4X10 LITRE BOXES IN THE DEVICE!

- 4x10 litre concentrate Bag-in-Box in the device
- 4 drink selection buttons + chilled water
- Preselection Hot – OPTIONAL (model Hot&Cold)
- Preselection CO₂ – OPTIONAL (model CO₂)
- 1 central drink exit with LED lighting (hygienic tempered glass tube)
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Reliable and durable – premium materials, robust surfaces
- Ease of use – easy refilling, programming, service and cleaning
- Perfect mixing result through patented MidMix®-system
- Multilingual LCD-Info Display (except ECO model)
- Preparation for payment systems + accounting (except ECO model)
- Customized front with your own design – OPTIONAL



Available in the following versions:

JDM WM 4 ECO, JDM WM 4 STILL, JDM WM 4 CO₂, JDM WM 4 Hot & Cold

Intelligent central
drink dispensing
area with LED,
dispensing height
suitable for bottles



Anti-
vandalism
buttons

TECHNICAL DATA & PRICES

DATA	JDM WM 4 STILL	JDM WM 4 CO ₂	JDM WM 4 Hot & Cold
Art. Nr.	frucB0421	frucB0422	frucB0423
Width	725 mm	725 mm	725 mm
Height	735 mm	735 mm	735 mm
Depth	325 mm	325 mm	325 mm
Exit height	160 mm - 310 mm	160 mm - 310 mm	160 mm - 310 mm
Weight	59 kg	61 kg	61 kg
Product selection buttons (incl. water)	5	6	6
Automatic caraffe preselection (extra)	OPTIONAL	OPTIONAL	OPTIONAL
ESI product labels ²	✓	✓	✓
Mixing ratio concentrates	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49
Concentrates in machine	4x10lt	4x10lt	4x10lt
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Cooling capacity	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	230 W	320 W	2.600 W
with CO ₂ -carbonator	-	✓	-
FSS ¹	✓	✓	✓
Flowmeter (water)	✓	✓	✓
Dispensing area LED light	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓	✓
Payment systems	Parallel/EXE	Parallel/EXE	Parallel/EXE
Monitoring Sanitation / Cleaning Interval	✓	✓	✓
Syrup Injection Valve (SIV ³)	✓	✓	✓
Automatic cup sensor	OPTIONAL	OPTIONAL	OPTIONAL
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL

*Installation of
water reduction
necessary

ALL our models are equipped with the unique and patented mixing system MidMix II.

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV = syrup injection valve for perfect mixing result

SIZE INCL. PACKAGING	JDM WM 4 STILL	JDM WM 4 CO ₂	JDM WM 4 Hot & Cold
Width	- mm	- mm	- mm
Height	- mm	- mm	- mm
Depth	- mm	- mm	- mm
Weight incl. Packaging	59 kg	61 kg	61 kg
MACHINE PACKAGE/PALLET			
Europallet 80 x 120 cm	3	3	3
UK-size pallet 100 x 120 cm	-	-	-



Save
resources



Save on Warehousing
and Transport



Save
energy



Reduce CO₂
emissions



MADE IN AUSTRIA