

AFFORDABLE AND VERSATILE

JDM ID 2 - smart design - easy refill- automatic cleaning!
Perfect for small hotels, buffets, offices and kiosks.

- Space for 2 x 5 Liter Bag-in-Box (WxHxD:230x200x300 mm) in the device
- 2 drinks + chilled water
- Slim design for plenty of counter space (WxHxD:260x590x470mm)
- Preselection CO₂ or HOT-OPTIONAL
- Central drink exit with LED-lighting (hygienic tempered glass tube)
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control for dosage and quantity
- Reliable and durable-premium quality materials
- Robust surfaces, stainless steel and metal
- Easy handling- fast refill
- Perfect mixing result due to patented MidMix® - technology
- Flexible programming to fulfill customer requirements
- Multilingual LCD-Info Display for customer information
- Incl. accounting and preparation for payment systems
- Maintenance-free dry cooling unit, high capacity



Space for
2 x 5l
Bag-in-Box

Available in the following versions:

JDM ID 2 STILL ECO, JDM ID 2 STILL, JDM ID 2 CO₂,
JDM ID 2 Hot & Cold

ESI (easy-slide-in)
Product labels



Anti-
Vandalism
Buttons

TECHNICAL DATA

DATA	JDM ID 2 STILL	JDM ID 2 CO ₂	JDM ID 2 Hot & Cold
Art. Nr.	frucB0231	frucB0232	frucB0233
Width in mm	260 mm	260 mm	260 mm
Height in mm	590 mm	590 mm	590 mm
Depth in mm	470 mm	470 mm	470 mm
Exit height	160 - 240 mm	160 - 240 mm	160 - 240 mm
Weight	30 kg	34 kg	32 kg
Product selection buttons (incl. water)	3	4	4
aut. caraffe preselection (Extra)	OPTIONAL	OPTIONAL	OPTIONAL
ESI product labels	✓	✓	✓
Flavours	2	2	2
Mixing ratio concentrates	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49
Bag-space dimensions BxTxH	230x200x300 mm	230x200x300 mm	230x200x300 mm
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Cooling capacity	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	230 W	320 W	2.600 W
with CO ₂ -carbonator	-	✓	-
FSS ¹	✓	✓	✓
Flowmeter (water)	✓	✓	✓
Dispensing area LED light	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓	✓
Activation function	OPTIONAL	OPTIONAL	OPTIONAL
Payment systems	OPTIONAL	OPTIONAL	OPTIONAL
Monitoring Sanitation/ Cleaning Interval	✓	✓	✓
Syrup Injection Valve (SIV ³)	✓	✓	✓
Automatic cup sensor	OPTIONAL	OPTIONAL	OPTIONAL
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL

All our models are equipped with the unique and patented mixing system MidMix II.

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV = syrup injection valve for perfect mixing result

**Installation of water reduction necessary*

SIZE INCL. PACKAGING	JDM ID 2 STILL	JDM ID 2 CO ₂	JDM ID 2 Hot & Cold
Width	570 mm	570 mm	570 mm
Height	570 mm	570 mm	570 mm
Depth	300 mm	300 mm	300 mm
Weight incl. Packaging	32 kg	36 kg	34 kg
MACHINE PACKAGE/PALLET			
Europallet 80 x 120 cm	8	8	8
UK-size Pallett 100 x 120 cm	12	12	12

