

MINIMUM SPACE & MAXIMUM PERFORMANCE!

THE JDM AQUA KEEPS YOU HYDRATED ALL THE TIME - AT THE PRESS OF A BUTTON!

- 4 direct selection buttons
- Available with CO₂:
for chilled water, ambient water, sparkling water and medium sparkling water
- Available with Hot&Cold:
for chilled water, ambient water, hot water and warm water
- 1 central drink exit with LED lighting (hygienic tempered glass tube)
- Fully electronic control of output quantities
- Reliable and made-to-last – premium materials, robust surfaces
- Ease of use – easy programming, service and cleaning
- Usable with tankset + gallon or direct water connection
- Multilingual LCD-Info Display
- Preparation for payment systems + accounting
- Carafe switch for quick serving by service staff - OPTIONAL

Available in the following versions:

JDM AQUA CO₂, JDM AQUA Hot & Cold



Anti-vandalism buttons



Space for carafs

TECHNICAL DATA & PRICES

DATA	JDM AQUA CO ₂	JDM AQUA Hot & Cold
Price in € excl. VAT	€	€
Art. Nr.	frucB0245	frucB0246
Width	260 mm	260 mm
Height	360 mm	360 mm
Depth	420 mm	420 mm
Exit height	240 mm	240 mm
Weight	25 kg	23 kg
Preselections	0	0
Product selection buttons (incl. water)	4	3
ESI product labels ²	✓	✓
Flavours	-	-
Mixing ratio concentrates	-	-
Concentrates in machine	0	0
Dosage of product selection	150-500ml / PULS	150-500ml / PULS
Cooling capacity	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	320 W	2.600 W
with CO ₂ -carbonator	✓	-
FSS ¹	✓	✓
Flowmeter (water)	✓	✓
Dispensing area LED light	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓
Monitoring Sanitation / Cleaning Interval	✓	✓
Syrup Injection Valve (SIV ³)	-	-
Water gallon + pumpset	OPTIONAL	OPTIONAL

ALL our models are equipped with the unique and patented mixing system MidMix II.

1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.

2) ESI = easy slide in: for fast and easy change of product labels

3) SIV = syrup injection valve for perfect mixing result

SIZE INCL. PACKAGING	JDM SLIM AQUA CO ₂	JDM SLIM AQUA Hot & Cold
Width	570 mm	570 mm
Height	465 mm	465 mm
Depth	310 mm	310 mm
Weight incl. Packaging	27 kg	25 kg
MACHINE PACKAGE/PALLET		
Europallet 80 x 120 cm	8	8
UK-size pallet 100 x 120 cm	12	12

